



MERCURY

TwoStroke

www.mercurymarine.com

TwoStroke Outboard Engines



All Round Reliability

Mercury's proven TwoStroke engines deliver easy starting, gutsy performance, and great all-round reliability. Across the range you'll find an array of features that help keep your boating experiences more enjoyable and trouble-free. Features such as largest engine capacity displacement, giving you more low-end thrust, advanced carburettor design and fully-regulated, high output alternators powering all your marine electronics will ensure absolute boating excellence.



2.5 - 30 HP Portable Power

Mercury's portable TwoStroke engines are lightweight and powerful, start easily with the modular electronic ignition and are part of the widest choice of portable power in the industry.



40 - 50 HP Mid-range Reliability

The secret to our mid-range TwoStrokes is our renowned reliability thanks to its cool running. With high volume, low pressure, floppy-vane water impellers keeping operating conditions down.

Specifications

Models	Max RPM	Cylinders	Displacement	Starting	Alternator System	Gear Ratio	Dry Weight	Shaft Length*	Trim Positions	Made In
50 HP	5150-5850	L-3	0.69L	Manual	11 amp, 130W	1.85 : 1	72kgs	S - L	6	JPN
40 HP	5000-5700	L-3	0.69L	Manual or Electric	11 amp, 130W	1.85 : 1	72kgs	S - L - XL	6	JPN
30 HP	5150-5850	L-2	0.43L	Manual or Electric	7 amp, 80W	1.92 : 1	51kgs	S - L	5	JPN
25 HP	5000-6000	L-2	0.43L	Manual or Electric	7 amp, 80W	1.92 : 1	51kgs	S - L	5	JPN
15 HP	5200-5800	L-2	0.29L	Manual	7 amp, 80W	1.85 : 1	41kgs	S - L	6	JPN
9.9 HP	4500-5300	L-2	0.25L	Manual	7 amp, 80W	1.85 : 1	41kgs	S - L	6	JPN
9.9 HP	5000-6000	L-2	0.17L	Manual or Electric	7 amp, 80W	2.08 : 1	26kgs	S - L	6	JPN
8 HP	4500-5500	L-2	0.17L	Manual	7 amp, 80W	2.08 : 1	26kgs	S - L	6	JPN
6 HP	4500-5500	L-2	0.17L	Manual	7 amp, 80W	2.08 : 1	26kgs	S - L	6	JPN
5 HP	4500-5500	L-1	0.10L	Manual	5 amp, 60W	2.15 : 1	20kgs	S - L	6	JPN
4 HP	4500-5500	L-1	0.10L	Manual	5 amp, 60W	2.15 : 1	20kgs	S	6	JPN
3.3 HP	4500-5500	L-1	0.075L	Manual	N/A	2.15 : 1	13kgs	S	4	JPN
2.5 HP	4200-5200	L-1	0.075L	Manual	N/A	1.85 : 1	12.5kgs	S	4	JPN

*Please refer to installation drawings for actual dimensions.

